



Step Up to a New Level of Comfort and Productivity

Our new stand-on mower series combines speed, agility and a high quality of cut for comfort and unprecedented performance.

Step on the brand new SRS™ Z2 Soft Ride Stand-On Mower, and you may not want to get off. That's because the SRS Z2 mower has raised the bar with its patent-pending operator platform featuring suspension technology for optimal operator comfort and unparalleled productivity.



Expanding on our zero-turn lineup of commercial lawn mowers, the SRS Z2 mower delivers the kind of heightened productivity that has become synonymous with the Ferris brand. Precision-engineered for superior maneuverability and balanced stability and traction, the ergonomically designed SRS Z2 mower is loaded with innovative features that live up to Ferris' unwavering commitment to quality.

Ride-On Warranty¹

Each customer has different needs, so Ferris created the 2+2 Year limited warranty. One simple warranty covers all our ride-on mowers for four years (48 months) or 500 hours, whichever occurs first. During the first two years (24 months), the mower is covered for unlimited hours. Belts, tires, brake pads, battery and blades are covered for 90 days.



Suspension Warranty¹

All consumers who purchased a Ferris riding mower with suspension will have the coil over shocks and all suspension-related components covered for 4 years (48 months), unlimited hours.

This warranty works in conjunction with the Ferris 2+2 commercial warranty to add an additional two years unlimited hours to the unit's suspension system.

We are committed to providing performance, productivity and durability.



¹See operator's manual or dealer for complete warranty details. Refer to engine operator's manual for engine warranty details.

NEW! SRS Z²



Very Smooth Stander ★★★★★

"Overall very smooth ride. Less jolt to body on uneven terrain than other stander units. Trim ability is good. Speed control setting is a great feature when working with different operators. Very good machine."

Tommy / Yorkville, IL

Model	5901466	5901465	5901468	5901467
Engine	Kawasaki® FX801V	Vanguard™ 810 EFI	Kawasaki® FX801V	Vanguard™ 810 EFI
Deck	52" iCD™	52" iCD™	61" iCD™	61" iCD™

The Soft Ride Stand-on SRS™ Z2 is raising the bar with our patent pending adjustable operator platform, featuring suspension technology, optimizing operator comfort and increasing productivity!

The superior balance provides stability and maneuverability that exceeds expectations for traction and handling.

The Soft Ride Stand-on SRS™ Z2 is designed to allow for quick operator exit and re-entry. Need to walk away from the mower to move an obstacle or debris? The PTO will automatically disengage when the operator leaves the platform. Restarting the blades is just as easy. When the operator steps back onto the platform and reengages the PTO switch they can continue mowing.



ENGINE

- Two-stage industrial air-cleaner
- Easy-to-use oil drain
- Rugged 7.75-gallon fuel tank

MOWER DECK

- iCD™ Cutting System with striping kit
- Hand-operated height-of-cut control adjusts in 1/4" increments from 1.75" - 5"
- Spindles with greaseable bearings for longer usable life: cast-iron greaseable (61"), aluminum greaseable (52")

DRIVE TRAIN

- Dual commercial Hydro-Gear® ZT-3400® Transaxles feature 7" cooling fans that assist with repelling debris
- Easy locking 3-position speed control setting
- Large turf friendly 23" tire for increased traction and performance
- 13" flat-free caster tires

SPEED


- Ground speed up to 10 mph

OPERATOR SYSTEMS

- Patent pending adjustable operator platform optimizes comfort
- Ergonomic control panel features integrated forward and reverse levers with dual stabilizer bars
- Ergonomic thigh pad is designed for improved comfort
- Automatic PTO disengagement
- Hour meter, fuel level gauge

ACCESSORIES

- Mulch kit



The patent pending suspension platform system is adjustable for a large range of weights and operating conditions, optimizing operator comfort and increasing productivity.



Height of cut is easily changed from the operator compartment for no hassle curb climbing and trailer loading.



Generous 7.75-gallon fuel tank is centrally located for consistent balance, and the fuel filler neck is conveniently located on the side for easy filling.



The easy locking 3-position speed control setting is conveniently located and requires no tools to facilitate smooth operation in a wide range of conditions.



Commercial Hydro-Gear® ZT-3400® Transaxles are designed for high performance and are fully serviceable.



Ergonomically designed thigh pad provides superior operator comfort, especially on uneven terrain.

