



**MERLIN**



FLAIL MOWER

# MERLIN XTREME OFFSET

- MERLIN XTREME OFFSET 1200**  
- 1.20m (3'11") working width
- MERLIN XTREME OFFSET 1600**  
- 1.60m (5'3") working width
- MERLIN XTREME OFFSET 2000**  
- 2.00m (6'7") working width



## MERLIN XTREME OFFSET SERIES

MODEL	MERLIN XTREME OFFSET 1200	MERLIN XTREME OFFSET 1600	MERLIN XTREME OFFSET 2000
<b>Specification</b>			
Working width	1.20m (3'11")	1.60m (5'3")	2.00m (6'7")
Cutting height	15mm-155mm	15mm-155mm	15mm-155mm
Cutting capacity	50mm	50mm	50mm
<b>Tractor requirement &amp; attachment</b>			
HP requirement	50	60	70
Method of attachment	3-point linkage	3-point linkage	3-point linkage
<b>Dimensions</b>			
Weight	1010kg	1060kg	1150kg
<b>Equipment details</b>			
PTO speed	540/1000rpm	540/1000rpm	540/1000rpm
Protection	Slip clutch	Slip clutch	Slip clutch
Number of flails	38	48	66
Hydraulic adjustment range	90° up, 60° down	90° up, 60° down	90° up, 60° down



# PROFESSIONAL OFFSET MOWING

Combining the power and durability of the Merlin range with a heavy-duty offset, these machines deliver exceptional results for busy verge mowing professionals.

A choice of cutting widths from 1.2m to 2.0m is available, as well as advanced features such as hydraulic safety breakaway, 120 degrees of head movement, and front or rear mounting.

## KEY FEATURES

Precision-engineered in the UK and created for contractors, local government, and highway maintenance teams, Merlin Xtreme Offset machines can tackle vegetation up to 50mm thick and feature a 150 degree hydraulic floatation system.

- 1.2m, 1.6m, 2.0m working widths
- Three-point linkage mounting
- Front or rear mounting
- 600mm hydraulic offset adjustment
- 540 or 1,000rpm PTO speed
- Hydraulic floatation system (+90° to -60°)
- Robust build quality
- PTO over-run protection
- Hydraulic safety breakaway
- 50mm cutting capacity
- Left or right hand cut options
- Replaceable full-length skids

